





COLIBRÌ - PVC tarpaulin

Welded and bolted structural steelwork protected with hot-dip galvanization, with "V" shaped support columns complete of base plate and accessories.

Material S235JR-S275JR-S355JR UNI EN 10025-1/2, grade 8.8 bolting material.

DELIVERY TIME: 3 WEEKS FROM EXW ORDER

VALIDITY PRICES FROM 04-2023 TO 12-2023

€ 2,350.00 VAT EXCLUDED

TECHNICAL SPECIFICATIONS

Dimensions	5,00x5,00 m
Square Meters	25 m²
Useful height	2,00 m
Step columns	5,00 m
Wind	25 m/s
Antiseismic	YES
Covering	PVC tarpaulin

Metal Working

Galvanized, pre-painted, shaped metal sheets for ridges, corner joints, flashings and eaves and any other necessary element.

Painting

Hot-dip galvanized coating UNI EN ISO 1461:2009.

Covering

Roof covering in self-extinguishing PVC coated 1100 Dtex polyester fabric, with a glossy lacquered finish on both sides.

OPTIONAL PRODUCTS

EV CHARGING STATION

EV charging station with no. 2 socket outlet, floor standing, connected to the user's distribution network (optimizable with PV), complete with access badge reader, power 7kW, 32 A.

"WIRE" SIDE CLADDING

 $\label{thm:complete} \textit{Vegetation support made of steel cables complete with turn buckles and stainless steel accessories.}$

"ECO-BRISE" SIDE CLADDING

Cladding made of wood-plastic composite slats.

"WIRE" BACK SIDE CLADDING

Vegetation support made of steel cables complete with turnbuckles and stainless steel accessories.

"ECO-BRISE" BACK SIDE CLADDING

Cladding made of wood-plastic composite slats.

COLOR STRUCTURE

galvanization

Other colors depending on availability. The colours here shown are purely indicative and may result different in reality

COLOR COVERING

