

CARPORT PHOTOVOLTAIC

COLIBRI - Sandwich panels

Welded and bolted structural steelwork protected with hot-dip galvanization, with "V" shaped support columns complete of base plate and accessories.
Material S235JR-S275JR-S355JR UNI EN 10025-1/2, grade 8.8 bolting material.

DELIVERY TIME: 3 WEEKS FROM EXW ORDER

VALIDITY PRICES FROM 07-2020 TO 12-2020



€ 0.00 VAT EXCLUDED

TECHNICAL SPECIFICATIONS

Dimensions	5,00x5,00 m
Square Meters	25 m ²
Useful height	2,00 m
Step columns	5,00 m
Wind	25 m/s
Antiseismic	YES
Covering	Sandwich panels

Metal Working

Galvanized, pre-painted, shaped metal sheets for ridges, corner joints, flashings and eaves and any other necessary element.

Painting

Hot-dip galvanized coating UNI EN ISO 1461:2009 finished with powder coating.

Covering

Roof in sandwich panels consisting of two galvanised sheet layers filled with an inner core of polyurethane foam (PUR).

Photovoltaic

Inverter power 3,3 Kw. Photovoltaic system installed on no. 1 canopy module.

OPTIONAL PRODUCTS

FOUNDATION CAGE

Foundation cage complete with welded steelwork in tubular profile covered with aluminum sheet.

Material S235JR-S275JR-S355JR UNI EN 10025-1/2.

EV CHARGING STATION

EV charging station with no. 2 socket outlet, floor standing, connected to the user's distribution network (optimizable with PV), complete with access badge reader, power 7kW, 32 A.

LED STRIP LIGHT WITH PRESENCE DETECTOR

LED strip light complete with aluminum housing. Voltage 24 Vdc.


Complete with presence detector.

COLOR STRUCTURE



Other colors depending on availability. The colours here shown are purely indicative and may result different in reality.

COLOR COVERING



Other colors depending on availability. The colours here shown are purely indicative and may result different in reality.